

DECLARATION OF PERFORMANCE**DoP No.: 2873-CPR-M529-19-EN**

1. Unique identification code of the product-type:
B+BTEC Injection System BIS-V
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-23/0765 Annex A3**Expiration date/Batch number: see packaging of the product.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type:	Injection mortar for bonding of post-installed rebar connections in concrete
For use in:	Concrete C12/15 to C50/60 acc. EN 206-1:2013 + A1:2016 Rebars Ø8 - Ø32 Tension anchors M12 - M24
Option/category:	EC2-1-1:2004+AC:2010, EC2-1-2:2004+AC:2008 Annex B2 and B3 (EAD 330087-01-0601)
Loading:	Static, quasi-static and fire
Material(s):	Rebars class B or C acc. EN 1992-1-1/NA Tension anchors steel, zinc plated acc. EN ISO 683-4:2018 or EN 10263:2017 Tension anchors stainless steel 1.4362, 1.4401, 1.4404, 1.4571 acc. EN 10088-1:2014 Tension anchors high corrosion resistant steel 1.4529, 1.4565 acc. EN 10088-1:2014
Temperature range(s):	-40°C to +80°C (max. short +80°C and max. long term +50°C)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

B+BTEC International, Munterij 8, 4762AH, Zevenbergen, The Netherlands

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): N.A.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the Declaration of Performance concerning a construction product covered by a harmonised standard: N.A.

8. In case of the Declaration of Performance concerning a construction product for which a European Technical Assessment has been issued:

Deutsches Institut für Bautechnik (DIBt) has issued the**European Technical Assessment ETA-23/0765**

on the basis of

EAD 330087-01-0601 used as a European Assessment Document

The Notified Body 2873 performed

third-party tasks, as described in Annex V of System 1,
and has issued Certificate of Conformity 2873-CPR-M 529-19

DECLARATION OF PERFORMANCE

DoP No.: 2873-CPR-M529-19-EN


9. Declared performance:

Essential Characteristics	Performance	Technical Docs/ Harmonized Standard
<i>Amplification factor, reduction factor and bond strength (static, quasi-static and fire)</i>	See Annex C1, C2, C3	Product Information Datasheet BIS-V 12-2023 EAD 330087-01-0601 ETA-23/0765
<i>Min. concrete cover, max. embedment depth</i>	See Annex B4, B5	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



R.G.W. van den Boogaart
General Manager

(Name and title)



G.A. Kant
Q.A. Manager

Zevenbergen, November 2023

(Place and date of issue)